

FlexWrapp Coating Gun Series

Adjustable Coating Lengths up to 1000 mm

Designed for ultimate precision

MELTON FlexWrapp Coating Gun Series is designed for continuous applications that require frequent width changes with maximum precision to reduce adhesive usage. The FlexWrapp Laminating Series offers improved reliability and has been specifically engineered to meet the demanding needs of the woodworking environment.

MELTON's FlexWrapp Series :

- Designed to ensure a consistent and smooth application for exact adhesive-film coating.
- Easy coating width adjustment up to 1000 mm.
- RTD sensing and proportional temperature control for an error margin up to 0.5°C (1°F).
- Optional Teflon® coating to prevent build-up for an easy-to-clean surface.
- Maximum durability for minimized labor and maintenance costs.




Easy to use width regulation system, bilateral, independent, and with just one operational side.

Suitable for work with special adhesives.



Optional filter.

Small, light and manipulable.



Adjustable valve system to supply the flow needed.



Available with roller bracket and position guide. Lip pressure control designed for fragile materials.

FlexWrapp Coating Gun Series



The **MELTON** FlexWrapp Series is ideal for wood profile applications, paper converting and profile wrapping. Precise adjustments allow for a superior quality application with excellent results.

A TOTAL PACKAGE

MELTON® offers a complete selection of hot melt components and support equipment:

- RTD hot melt hoses
- Manual and automatic dispensing valves
- Nozzle and applicator styles
- Mounting bracket packages
- Solid-state pattern control systems
- In-line filters
- Compatible replacement parts
- High-performance hot melt adhesives
- Cost-effective rebuild/exchange programs

Technical Specifications

FlexWrapp Characteristics	
Maximum Coating Length	Up to 1000 mm
Temperature Control	PT - 100/ NI - 120/ FEKO
Coating Thickness Range	0.025mm - 1mm
Maximum Operating Temperature	240°C
Maximum Operating Pressure	100 bar
Max. Operating Speed	150 m/min
Dimensions	180 mm x 150 mm x (depending on the configuration)



Web: www.limteknikk.no E-mail: info@limteknikk.no Tel: (+47) 918 91 400

For more information visit www.valcomelton.com or contact your local representative.

World Headquarters: USA, Cincinnati, Ohio (Corporate Offices) • Tel: 513.874.6550 • Fax: 513.874.3612 • info@valcomelton.com

European Headquarters: Spain, Navarra • Tel: +34.948.321.580 • Fax: +34 948 326 584 • melton@melton.es

Asian Headquarters: China, Xiamen, Fujian • Tel: +86.592.591.7854 • Fax: +86.592.591.7834 • china@valcomelton.com

www.valcomelton.com • Serving Over 52 Countries Worldwide.

