



NC-24

Compatible Extrusion and Spray Handguns

- Ideal for hot-melt dispensing of adhesives, sealants and other materials
- Swirl handguns permit precise placement and volume of glue pattern
- Temperature range is easily adjustable up to 400° F (200° C)
- Spray guns include mechanical swirl-spray air activation when trigger is engaged
- Extrusion handguns utilize a large ball-and-seal and larger flow paths for use with high-viscosity or filled materials
- Compliance with major approval codes worldwide



A durable, lightweight handle and molded high-temp nylon shell protects the operator from heated components and allows for easy operation.



A 360-degree hose swivel allows for optimum movement and eliminates hose twisting.



A wide variety of handgun nozzles (both standard and extended) with varying orifice diameters are available including multi-orifice nozzles.



*Two models are available for top-feed extrusion and swirl-spray

Specifications

Patterns	Extrusion and swirl-spray
Maximum Operating Temperature	400 F (200 C)
Electrical Requirements	120 or 240, VAC 50/60 Hz
Spray Air Pressure	0 to 15 psi
Maximum Air Consumption	1.2 scfm
Standard Extrusion	0.020 to 0.093
Nozzle Diameter	(0.5 to 2mm)



For more information, visit <http://hub.am/19kJaSp> or contact your local Valco Melton representative.

World Headquarters: USA, Cincinnati, Ohio (Corporate Offices) • Tel:+1.513.874.6550 • Fax: +1.513.874.3612

Europe Headquarters: Spain, Navarra • Tel:+34.948.321.580 • Fax:+34.948.326.584

Asia Headquarters: China, Xiamen, Fujian • Tel:+86.592.591.7854 • Fax:+86.592.591.7834

info@valcomelton.com • Serving over 76 Countries Worldwide • valcomelton.com